


## VORISOLIERTE BOGEN 45°



VORGEFERTIGTE  
BOGEN

GESCHMIEDETE  
BOGEN

Stahlrohr		SERIE 1 PEHD ROHR	SERIE 2 PEHD ROHR	SERIE 3 PEHD ROHR	Standar- dlänge	Zusätzliche Länge	Asymmetrische	
DN	d [mm]	De [mm]	De [mm]	De [mm]	L1=L2 [mm]	L1=L2 [mm]	L1 [mm]	L2 [mm]
20	26,9	90	110	125	420	1000	420	1500
25	33,7	90	110	125	420	1000	420	1500
32	42,4	110	125	140	465	1000	465	1500
40	48,3	110	125	140	465	1000	465	1500
50	60,3	125	140	160	490	1000	490	1500
65	76,1	140	160	180	510	1000	510	1500
80	88,9	160	180	200	530	1000	530	1500
100	114,3	200	225	250	610	1000	610	1500
125	139,7	225	250	280	610	1000	610	1500
150	168,3	250	280	315	760	1000	760	1500
200	219,1	315	355	400	760	1000	760	1500
250	273,0	400	450	500	875			
300	323,9	450	500	560	1050			
350	355,6	500	560	630	585			
400	406,4	560	630	710	650			
450	457,0	630	710	800	670			
500	508,0	710	800	900	700			
600	610,0	800	900	1000	740			
700	711,0	900	1000	1100	1500			
800	813,0	1000	1100	1200	2000			