

ECOALUPEX

ECOALUPEX is our pre-insulated flexible piping system designed for district heating systems



ECOALUPEX SINGLE - HEATING PN 10 - STANDARD INSULATION

Type [mm]	Multilayer Pipe			PE casing		Min. bending radius [m]	Pipe weight [kg/m]	Fluid content [l/m]	Maximum roll length * [m]
	d _{int} [mm]	wt [mm]	d _{ext} [mm]	D _e [mm]	wt _p [mm]				
20/90	16	2,0	20	90	3,0	0,80	0,9	0,20	-
25/90	20	2,5	25	90	3,0	0,80	1,0	0,31	-
32/90	26	3,0	32	90	3,0	0,80	1,2	0,53	-

* On request.

ECOALUPEX TWIN - HEATING PN 10 - STANDARD INSULATION

Type [mm]	Multilayer Pipe			PE casing		Min. bending radius [m]	Pipe weight [kg/m]	Fluid content [l/m]	Maximum roll length * [m]
	d _{int} [mm]	wt [mm]	d _{ext} [mm]	D _e [mm]	wt _p [mm]				
20+20/110	16	2,0	20	110	3,0	0,85	1,4	0,40	-
25+25/110	20	2,5	25	110	3,0	0,85	1,6	0,63	-
32+32/110	26	3,0	32	110	3,0	0,85	2,0	1,06	-

* On request.