



ECOPEX FORTE 16

ECOPEX FORTE 16 is our pre-insulated flexible piping system designed for small to medium-sized district heating networks.

ECOPEX FORTE 16 UNO - SERIES 1

Type [mm]	ECOPEX FORTE 16		PE casing		Min. bending radius [m]	Fluid content [l/m]	Maximum roll length* [m]
	External diam. [mm]	Internal diam. [mm]	External diam. [mm]	Internal diam. [mm]			
40/90	40.0	32.6	90	3,0	0,80	0,83	400
50/110	49.8	40.8	110	3,0	0,85	1,31	300
63/125	61.8	51.4	125	3,0	0,90	2,07	300
75/140	72.8	61.4	140	3,0	1,00	2,96	250
90/160	86.5	73.6	160	3,0	1,10	4,25	150
110/160	104.9	90.0	160	3,0	1,10	6,36	150
125/180	117.0	102.2	180	3,0	1,40	8,20	90
140/200	130.4	114.6	200	3,2	1,40	10,31	70

* The maximum length is based on a coil with a diameter of 2.80 m and a width of 1.20 m.

ECOPEX FORTE 16 DUO - SERIES 1

Type [mm]	ECOPEX FORTE 16		PE casing		Min. bending radius [m]	Fluid content [l/m]	Maximum roll length* [m]
	External diam. [mm]	Internal diam. [mm]	External diam. [mm]	Internal diam. [mm]			
40+40/125	40.0	32,6	125	3,0	0,90	1,67	300
50+50/160	49.8	40,8	160	3,0	1,00	2,61	150
63+63/180	61.8	51,4	180	3,0	1,20	4,15	90
75+75/200	72.8	61,4	200	3,0	1,30	5,92	70

* The maximum length is based on a coil with a diameter of 2.80 m and a width of 1.20 m.